

Stratasys Origin[®] One

General

Technology	Programmable PhotoPolymerization P3™
Materials	Photocurable materials from Stratasys ecosystem material partners. Refer to Stratasys website for an up-to-date selection.
Build Envelope (XYZ)	192 x 108 x 370 mm / 7,672 cm ³ (7.5 x 4.25 x 14.5 in. / 462 in ³) Maximum length on the diagonal — 220mm (8.6 in.)
Minimum Feature Size	Material and design dependent, as low as 50µm
Resolution	4K light engine
Process Energy	UV (385nm) and thermal
Software	Origin One cloud based web application
Regulatory Compliance	CE, FCC

Physical Footprint

System Size and Weight	49 x 51 x 113cm (19 x 20 x 44 in.) 81 kg (180 lbs.)
------------------------	--

Facility Requirements

Power Requirements	90–264 VAC, 50–60 HZ, 700 W, 1 phase
Network Connectivity	Ethernet / WiFi with secure network configuration
Ventilation	Refer to photopolymer material MSDS or contact Stratasys rep for guidelines.
Operating Conditions	Operating temperature 15°C to 30°C (59°F to 86°F) Operating Humidity 30% to 70%
Gas Input (optional)	Facility air or inert gases
Gas Exhaust (optional)	Facility exhaust

Material Handling

Resin Tray Capacity	2L
Resin Storage Temp	Typically 15°C to 30°C (59°F to 86°F)

Security Features

Printer Authentication	Cryptographically-secure handshake
Network Security	Industry-standard end-to-end encryption